

1,200 W Technical Specifications

AC INPUT

Voltage: 90—275VAC Over-voltage (tested to 300Vac)

Frequency: 47-63Hz

Peak Inrush Current: <20A

Power Factor: 0.99 typical

Efficiency: ~88% with 115VAC source, 50 to 100% load

Hold-Up Time: 20mS min.

Input Overcurrent: (internal) 20A Fuse

DC OUTPUT

Voltage: 12, 24V, 27V, 48V, 56V, 130 & 375Vdc. Custom outputs available, consult Factory.

Power: 1,200W

Accuracy: ± 50mV

Ripple & Noise: 1% V P-P Measured with 20Mhz Bandwidth

Line Regulation: Less than ±0.25%

Load Regulation: ±1.0% from no load to full load (droop load share)

Parallel Use: May be paralleled with other like units for increased system output, redundant diode included

Current Sharing: Slope program current share, (droop)

Temperature Coefficient: < ±0.02% per°C

Acoustic Noise < 55dBA at nominal input and full load

ELECTRONIC ALARMS (Basic Set, others available)

AC OK: low when AC input is in range

Output OK: low if the output voltage is within 10% of the actual voltage set point (low=<.6V@1mA) (high=open collector (I<50µA)

CAN Bus: available option

VISUAL FAULT INDICATORS

Output OK: A front panel Green "Output OK" LED will be lit if the unit's output is within the acceptable range.

ELECTRONIC CONTROL INPUTS

Remote Inhibit: Application of a TTL input signal will cause the supply to shut down and an output OK fault alarm will be issued. (TTL High = Inhibit)

Remote Program: Provides +9%, -27% of set point voltage with 0 to 5V control signal

TEMPERATURE

Normal Operation: -20 to +55°C

High Temperature Operation: derate 10% per°C, 55 to 65°C

Low Temperature Turn On: -40°C Minimum

Storage / Transportation: -40°C to +85°C

Humidity Operating: 5% to 95% RH non-condensing

Storage: 0% to 99% RH non-condensing

PHYSICAL DIMENSIONS

Packaging (both available in 1U and 2U)

Dimensions:

1U, H44.5 x W223 x D375mm (1.75 x 8.75 x D14.75")

2U H88x W122 x D375mm (3.5 x 4.2 x 14.75")

Weight: 4kg (9lbs)

AGENCY COMPLIANCE

CE Marked: Low Voltage Directive only

Electrical safety: IEC 60950-1, UL 60950-1

EMI (conducted): FCC Part 15, Sub-part J, class A and EN55022, class A

EMI (radiated): Stand alone module tested to EN55022 Class B.

Harmonics: EN 61000-3-2

EN 61000-6-1 (Immunity, light industry)

EN 61000-6-2 (Immunity, industry)

EN 61000-6-3 (Emissions, light industry)

EN 61000-6-4 (Emissions, industry)

RoHS compliant

Notes:

Designed for use with Mercury shelf or custom Backplane

Options:

Variable Speed Fan

Silicone RTV encapsulate

Contact Factory for Options and full Product Specification



ORDERING INFORMATION

Part no.	Description
136653-N48D00	1,200W, 1U, 48Vdc, Droop CS, standard alarms
136874-N54D00-LF	1,200W, 2U, 54Vdc, Droop CS, standard alarms
136874-P27D00	1,200W, 2U, 27Vdc, Droop CS, standard alarms
139239-P12A00	1,200W, 2U, 12Vdc, Active CS, standard alarms

www.tdipower.com

© Copyright 2007, Transistor Devices, Inc. 17536A

Energy Solutions for the Next Generation

This document is believed to be correct at time of publication and Transistor Devices, Inc. accepts no responsibility for consequences from printing errors or inaccuracies. Specifications are subject to change without notice.